Garrett Marine Inc.

10497 LONGWOOD DRIVE · LARGO, FLORIDA 33543 · TEL. (813) 393-6923

GARRETT 36 GPR FARR

Standard Equipment List

DEALER

Name:_____

Salesman:_____

Order Date:_____

Authorized Signature:

_____

CUSTOMER

Name_____

Address:_____

City:_____

State:_____Zip:_____

Telephone:_____

HULL AND DECK

CONSTRUCTION: Hand layed up fiberglass and Kevlar. Cored for rigidity. Mechanical fastening of deck, bedded with butyl and polysulfide. Non-skid pattern on horizontal surfaces.

KEEL: Lead, 3355 pound fin keel standard. Centerboard optional.

DECK DETAIL: Teak toe-rail from stemhead to chainplates. Clear anodized toe-rail with cars. Stainless double-rail bow and stern pulpits, thru-bolted stanchions and vinyl-covered 3/16" lifelines.

COCKPIT: Thru-wall fitting for manual bildge pump. 2 large self-bailing scuppers. Emergency tiller. 2 bulkhead mount compasses.

ACCOMMODATION

FINISH: Spacious Interior trimmed with hardwoods throughout. Cabin sole of teak and holly. Hatches for access to bildge.

BERTHS: 4" foam cushions with removable fabric covers. 2 adjustable pipe berths. 2 settee berths. 2 pilot berths.

Head: Marine head forward (enclosed). Marine toilet pumps to holding tank.

GALLEY: 2-burner alcohol stove (CNG available as an option). Deep, stainless steel sink with manual pump. Top-loading icebox with shelves and dividers(mechanical refrigeration available as an option).

NAVIGATOR'S STATION: Large navigation table with storage. Contoured seat and backrest. Large storage area for instruments, charts, tables and navigational equipment.

VENTILATION: Large foredeck hatch. 2 ports aft for ventilation of stern berths.

GARRETT 36 GPR FARR

STANDARD EQUIPMENT LIST (con't.)

MECHANICAL AND ELECTRICAL

POWER: 21 Hp. Westerbeke 4-cylinder diesel, self-bleeding, fresh-water cooled, cold weather starting aid, full instrumentation, primary and secondary fuel filter, 2:1 reduction. Special-alloy stainless shaft, interior stuffing box, external strut-bearing, 2-blade folding propeller. Water-lift exhaust.

ELECTRICAL: 55-Amp. alternator; two 90 deep charge batteries (third starting battery optional). 14-gauge stranded copper wiring minimun, solderless terminals, protected against chafe, into conduit where appropriate. Electrical panel with 6 circuit breakers 12 VDC, (AC power optional). Circuit breaker panel with battery level guage. Interior lighting; dome lights, flourescent lighting in galley, navigation lights meet IMCO requirements.

PLUMBING: Fuel tank 15 gallons; 35 gallons of water, manual galley pump. (Salt water pump in galley optional).

HARDWARE, SPARS, AND RIGGING

FRACTIONAL RIG: Welded masthead with internal halyards protected by a polyurethane paint. Roller bearing mainsheet traveler with 3:1 control. Double inboard genoa tracks with (4) cars; complete spinnaker gear; tri-sect masthead; dacron sheets; wire/rope running backstays; 4 locking winch handles.

WINCHES

Primaries (2) 2speed Barient 28's
Secondaries (2) 2 speed Barient 24's
Halyards (2) 2 speed self tailing Barient 23's

Specifications and prices subject to change without notice